







Mounting the stainless steel gutter, Multisserie.

Due to limitations in the production proces of punching curved stainless steel, the mounting holes in the new stainless steel gutter differ from the plastic ones.

Therefore an upgrade kit is available to be able to mount this gutter on the "old" curved panels. For contents, see last page.



Mounting instructions with upgrade kit.

1. Remove 4 screws M5x16. (philips 2)
2. Mount the template with the same 4 screws.
3. Drill 4 holes with the 4mm drill.
4. Remove the template.
5. Carefully bend the curved panel inwards on both sides of the square hole.
6. Do this with waterpumppliers (channellock) in three steps as shown.
7. See picture (5-7). *This is necessary to get some clearance on both sides of the gutter outlet. See detail 12.*
8. Tap M5 and reuse the M5 screws (preferred)
OR mount the new gutter with the delivered self tapping screws.
9. Slide the gutter as far as possible towards the hinge and tighten the screws. see detail 11. Leave a small clearance.
10. Mount 3 screws M5x12 in the remaining holes. (philips 2)
11. If necessary, pull the drainhose on the gutter outlet with snipe nose pliers.


Repeat this for all 3 doors.

In case it is preferred to mount the gutters on new adapted curved panels, these can be ordered with the part numbers, mentioned below. Note that the middle door has no grids in the curved panel and has therefore a different part number.



Exchanging plastic gutters, complete with curved panels.

1. Remove the 4 plastic finishing plugs. *It is almost impossible to get them out in one piece. Therefore, the easiest way is to carefully tick them inwards with a slotted screwdriver as shown on the picture.*
2. Unscrew the 4 screws (M5x45) behind the finishing plugs.
3. Take out the complete panel/gutter assembly.
4. Unscrew the M5x12 screws for reuse, and dispose the gutters and panels according local legislations.
5. Mount the new panel with the M5x45 screws with help of the nylon spacers.
6. Mount the gutter with the M5x12 screws. If necessary, pull the drainhose on the gutter outlet with snipe nose pliers.
7. Finish the holes with the finishing plugs.
8. Repeat this for all 3 doors.



12x 2005250 Finishing plug




Related parts that can be reused.

- 12x 4288232 Screw M5x12
- 12x 4280218 Screw M5x45
- 12x 9057347 Spacer 10mm, nylon
ø5xø10mm

Contents of service kit 9190173

The kit consists of :



1x 9194890 Drilling template.

1x 9191301 drill 4,0 mm

12x 4289976 Self tapping screw A4 4,8x13mm

9x 4288232 Screw M5x12

This instruction sheet

Carton box



Necessary tools:

(cordless) drill.

Normal set of tools in which:

Waterpump pliers

Screwdriver Philips nr2

Screwdriver slotted

Snipe nose pliers

