

# SERVICE INSTRUCTION

for service kit      **9191196s Lamp 120V**  
and                      **9191122s Lamp 240V**



Applied in:  
Deli Multiserie  
Bakery Multiserie



Contents service kit:

9191196 1x      Lamp 120V 150W (in USA versions)

or

9191122 1x      Lamp 240V 150W (in EUR versions)

and

3500040 1x      Seal, oven illumination

9192234 1x      Glass, oven illumination


**- NOTICE -**

This manual is prepared for the use of trained Service Technicians and should not be used by those not properly qualified. If you have attended a training for this product, you may be qualified to perform all the procedures in this manual.

This manual is not intended to be all encompassing. If you have not attended a training for this product, you should read, in its entirety, the repair procedure you wish to perform to determine if you have the necessary tools, instruments and skills required to perform the procedure. Procedures for which you do not have the necessary tools, instruments and skills should be performed by a trained technician.

Reproduction or other use of this Manual, without the express written consent of Fri-Jado, is prohibited.

## REPLACEMENT OF A LAMP



*Notice: Do not touch the lamps with bare hands. Use a clean cloth or paper tissues when replacing the lamp. Remove any moisture with alcohol or methylated spirits after the lamp has cooled down.*

1. Remove the plug from the wall socket.
2. Remove the 4 screws from the lamp holder. Beware, the frame, glass and gasket will come off at the same time.

Remove the lamp.

3. Push the lamp against the spring to one side of the lamp holder.
4. Pull it down.
5. Take it out.

Install a new halogen lamp .

6. First press one side of the lamp into one connection point.
7. Then put the lamp properly in its place.
8. Let it spring into the other connection point (as showed).
9. Make sure the lamp is properly clamped between the two connection points.
10. Install the gasket, glass and frame.
11. Before fastening the screws completely, move the glass to the middle of the frame. It is the intension that the glass corners do not touch the edge.

